

SLATER

Features

- Solid brass construction
- Face plate with 3-spoke circular handle
- Intended for use with Newport Brass rough valve(s) as specified (Required Accessory)
- 1.8 GPM (6.8 LPM) Max, Shower Only

Shower Trim 3-2924BP

Also 3-570

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- IPC
- Energy Policy Act of 1992
- EPA WaterSense
- California Energy Commission
- All applicable US Federal and State material regulations

Colors / Finishes

- 10B: Oil Rubbed Bronze
 15: Polished Nickel
 15S: Satin Nickel PVD
 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.











3-2924BP 3-570

Specified Model				
Model	Description	Colors Finishes		
3-2924BP	Shower Trim	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other		
3-570	Shower System Control Valve Trim (Escutcheon/Handle)	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other		

Required Accessory: Trim(s), above, and Rough Valve(s), below, must be specified.				
System Element	Shower (or Tub) Valve (Choose One)		Control Valve (Optional)	
Description	BP Valve Option A	BP Valve Option B	3-Outlet Diverter	
Inlet/Outlet Size	1/2"	1/2"	1/2"	
Part Number	1-594	1-684	1-703	
Image				

Product Specification: Add size designator and "Color / Finish" suffix to Model number, below.

The single-control Shower Trim shall be made of solid brass construction. Shower Trim shall include showerhead with arm and flange and faceplate with 3-spoke circular handle. Showerhead shall have a maximum flow rate of 1.8 gallons (6.8 liters) per minute. Shower Trim shall be Newport Brass Model 3-2924BP /____ and single-control Shower rough valve shall be Newport Brass Model 1-____. [Optional Shower System Control Valve Trim (Escutcheon/Handle) shall be 3-570/____ and Shower System Control Valve shall be 1-703].



3-2924BP

PRODUCT DIMENSIONS (Units are in inches)

Product Dimensions are provided for reference only. For specific product installation guidelines, please reference the Installation Instructions of the product being installed.

